



Echoflex ELEDR-AU

- Mounts through ½" knockout into J Box or fixture
- Communicates on 902 MHz frequency
- Controls up to 20A of lighting or miscellaneous electrical loads
- Controls up to 1.5HP @120VAC 3HP @ 240/277VAC of fan motor load
- Configurable through software or other mechanical means
- Transmission range of 24m (80 ft) up to 100m (330 ft) line of sight

DEVICE: ELEDR-AU 120-277		Echoflex Solutions, Inc. 38924 Queens Way Unit #1 Squamish, British Columbia Canada V8B 0K8 Phone: 1 (778) 733-0111 Toll Free: 1 (888) 324-6359 Fax: 1 (604) 815-0078 echoflexsolutions.com
MAXIMUM LOAD RATING: 20A @120-277V - 1.5HP @ 120V 3HP @ 240/277V		
MAXIMUM AMOUNT OF WIRELESS DEVICES CONNECTED: 20		
ELECTRICAL CONNECTION: WIRE LEADS 250mm (10.0")		
TITLE: POWER LOAD CONTROLLER 120-277V ELECTRICAL LOADS 1.5/3HP MOTOR LOADS	DOCUMENT NO: 9DC-9440	UNLESS OTHERWISE SPECIFIED - ALL DIMENSIONS ARE IN MILLIMETERS.

