


Echoflex ELED-BUN 120-277

- Mounts through ½" knockout into J Box or fixture
- Communicates on 902 MHz frequency
- 0-10V dimming capability up to 100mA of sinking current
- Controls up to 11.5A of lighting load
- Configurable through software or other mechanical means
- Transmission range of 24 m (80 ft) up to 100 m (330 ft) line of sight

| | | |
|---|----------------------------|---|
| DEVICE: ELED1-BUN 120-277 | | Echoflex Solutions, Inc. 38924 Queens Way Unit #1 Squamish, British Columbia Canada V8B 0K8 Phone: 1 (778) 733-0111 Toll Free: 1 (888) 324-6359 Fax: 1 (604) 815-0078 echoflexsolutions.com |
| MAXIMUM LOAD RATING: 11.5A @120-277V | | |
| MAXIMUM AMOUNT OF WIRELESS DEVICES CONNECTED: 20 | | |
| ELECTRICAL CONNECTION: WIRE LEADS 250mm (10.0") | | |
| TITLE: LED DIMMING CONTROLLER 120-277V LIGHTING LOADS WITH 0-10v DIMMING | DRAWING NO: 8DC-9755 Rev 2 |  UNLESS OTHERWISE SPECIFIED - ALL DIMENSIONS ARE IN MILLIMETERS. |