



## Echoflex ELED1H-xU 240-347

- Mounts through ½" knockout into J Box
- Communicates on 902 MHz frequency
- 0-10V dimming up to 100mA of sinking current
- Controls up to 20A @240/277VAC or 16A @ 347VAC of lighting loads
- Configurable through software or other mechanical means
- Transmission range of 24m (80ft) up to 100m (330ft) line of sight

DEVICE: ELED1H-AU 240-347		<b>Echoflex Solutions, Inc.</b> 38924 Queens Way Unit #1 Squamish, British Columbia Canada V8B 0K8 Phone: 1 (778) 733-0111 Toll Free: 1 (888) 324-6359 Fax: 1 (604) 815-0078 echoflexsolutions.com
MAXIMUM LOAD RATING: 20A @ 240/277VAC 15A @ 347VAC		
MAXIMUM AMOUNT OF WIRELESS DEVICES CONNECTED: 20		
ELECTRICAL CONNECTION: WIRE LEADS 250mm (10.0")		
TITLE: LED DIMMING CONTROLLER 240-347VAC LIGHTING LOADS WITH 0-10V DIMMING	DRAWING NO: 9DC-9426 Rev 1	UNLESS OTHERWISE SPECIFIED - ALL DIMENSIONS ARE IN MILLIMETERS.

