


## Elaho EDSSC-G2

- Mounts through ½" knockout into junction box or fixture
- Controls up to 2 20 A @ 120-277V of lighting loads
- 2 Fully isolated 0-10V dimming channels 100mA sinking current each
- 24VDC for occupancy sensor power 50mA maximum
- Configurable through mobile app or other mechanical means
- Supports up to 16 presets

### Notes:

- Cap all unused wires
- Controllers are for indoor use only
- Follow all local and National Wiring Code Regulations

DEVICE: EDSSC-G2		<b>Echoflex Solutions, Inc.</b> 38924 Queens Way Unit #1 Squamish, British Columbia Canada V8B 0K8 Phone: 1 (778) 733-0111 Toll Free: 1 (888) 324-6359 Fax: 1 (604) 815-0078 echoflexsolutions.com
PART NUMBER: 8187A1122		
MAXIMUM LOAD RATING: 2 x 20 A @ 120-277V		
ELECTRICAL CONNECTION: WIRE LEADS 250mm (10.0")		
TITLE: ELAHO 2 Zone Smart Space Controller	DRAWING NO: 9DC-9173	 an ETC Company
UNLESS OTHERWISE SPECIFIED - ALL DIMENSIONS ARE IN MILLIMETERS.		