


Echoflex ELED2-xU 120-277

- Mounts through ½" knockout into J Box
- Communicates on 902 MHz frequency
- 1 channel 0-10V dimming up to 100mA of sinking current
- 1 channel 0-10V CCT control of white LEDs
- Controls up to 20A of lighting load
- Configurable through software or other mechanical means
- Transmission range of 24m (80ft) up to 100m (330ft) line of sight

DEVICE: ELED2-xU 120-277		<div>Echoflex Solutions, Inc.</div> <div>38924 Queens Way Unit #1 Squamish, British Columbia Canada V8B 0K8 Phone: 1 (778) 733-0111 Toll Free: 1 (888) 324-6359 Fax: 1 (604) 815-0078 echoflexsolutions.com</div> <div></div> <div>UNLESS OTHERWISE SPECIFIED - ALL DIMENSIONS ARE IN MILLIMETERS.</div>
MAXIMUM LOAD RATING: 20A @120-277V		
MAXIMUM AMOUNT OF WIRELESS DEVICES CONNECTED: 20		
ELECTRICAL CONNECTION: WIRE LEADS 250mm (10.0")		
TITLE: TUNABLE WHITE DIMMING CONTROLLER 120-277V LIGHTING LOADS WITH TUNABLE WHITE & 0-10V DIMMING	DRAWING NO: 8DC-9919 Rev 1	