



## Echoflex ELED3H-xU 240-347

- Mounts through 1/2" knockout into J Box
- Communicates on 902 MHz frequency
- 3 Channels of 0-10V dimming up to 100mA of sinking current each
- Integrated daylight control on two channels
- Controls lighting load up to 20A @ 240-277V or 16A @ 347V
- Configurable through software or other mechanical means
- Transmission range of 24m (80ft) up to 100m (330ft) line of sight

DEVICE: ELED3H-xU 240-347		<b>Echoflex Solutions, Inc.</b> 38924 Queens Way Unit #1 Squamish, British Columbia Canada V8B 0K8 Phone: 1 (778) 733-0111 Toll Free: 1 (888) 324-6359 Fax: 1 (604) 815-0078 echoflexsolutions.com
MAXIMUM LOAD RATING: 20A @ 120-277V or 16A @ 347V		
MAXIMUM AMOUNT OF WIRELESS DEVICES CONNECTED: 20		
ELECTRICAL CONNECTION: WIRE LEADS 250mm (10.0")		
TITLE: TRI-ZONE DIMMING CONTROLLER 240-347V LIGHTING LOADS WITH 3 0-10v DIMMING ZONES	DRAWING NO: 9DC-9731 Rev 1	UNLESS OTHERWISE SPECIFIED - ALL DIMENSIONS ARE IN MILLIMETERS.