


ERDRC-FDU/EREB-AD

- ERDRC Mounts through 1/2" knockout into J Box or fixture
- EREB-AD mounts on a DIN rail (43880 & DIN EN 60715)
- 0-10V dimming capability up to 25mA of sinking current
- Controls up to 20A of lighting load
- Follow all local and National Wiring Code Regulations

DEVICE: ERDRC-FDU 120/347 - EREB-AD		Echoflex Solutions, Inc. 38924 Queens Way Unit #1 Squamish, British Columbia Canada V8B 0K8 Phone: 1 (778) 733-0111 Toll Free: 1 (888) 324-6359 Fax: 1 (604) 815-0078 echoflexsolutions.com
MAXIMUM LOAD RATING: ERDRC-FDU=20A @120V - 15A @347V - EREB-AP=20A @ 120/277VAC		
MAXIMUM AMOUNT OF WIRELESS DEVICES CONNECTED: 20		
ELECTRICAL CONNECTION: WIRE LEADS 250mm (10.0")		
TITLE: Dimming Controller for use with Emergency Lighting loads with 0-10V Dimming	DRAWING NO: 9DC-9375	 an ETC Company
UNLESS OTHERWISE SPECIFIED - ALL DIMENSIONS ARE IN MILLIMETERS.		